

---

# **bottle-gui**

***Release 0.2.1***

February 14, 2015



|          |                              |           |
|----------|------------------------------|-----------|
| <b>1</b> | <b>User documentation</b>    | <b>3</b>  |
| <b>2</b> | <b>API documentation</b>     | <b>5</b>  |
| 2.1      | bottle_gui package . . . . . | 5         |
| <b>3</b> | <b>Testing</b>               | <b>9</b>  |
| <b>4</b> | <b>Indices and tables</b>    | <b>11</b> |
|          | <b>Python Module Index</b>   | <b>13</b> |



Welcome in the bottle-gui documentation. This package is used to visualize services used in bottle web framework.



---

## User documentation

---

From the user's point of view, only thing you need to do is install the package and import one function:

```
pip install bottle-gui
```

And the code:


```
import bottle_gui
```

```
gui = bottle_gui.gui()
```

That's it! This will add the bottle gui service to your bottle namespace.

The `gui()` takes one optional parameter, which specifies where the GUI service should run. By default, it will run at `/.`

Now, all you have to do is to run your server and go to address of the service, where you should see something like:



Note, that this is only for test, in real scenario, there would be more URL's and their comments would be meaningful.



## API documentation

## 2.1 bottle\_gui package

`bottle_gui.bottle_gui.TEMPLATE_PATH = 'static/templates/'`  
Path to the template directory.

`bottle_gui.bottle_gui.read_template(template_name)`  
Read content of the template file.

**Parameters** `template_name` (*str*) – Name of the file.

**Returns** Content of *template\_name* from `TEMPLATE_PATH` directory.

**Return type** str

```
bottle_gui.bottle_gui.INDEX_TEMPLATE = '<HTML>\n<head>\n <title>API index</title>\n <link rel="stylesheet" type="text/css" href="static/templates/index.html">\n</head>\n<body>\n</body>\n</HTML>'
```

```
bottle_gui.bottle_gui.TABLE_TEMPLATE = '\n<table class="api_table">\n <tr>\n <th colspan="2" class="api_name">
```

```
static/templates/table.html
```

```
bottle_gui.bottle_gui.ROW_TEMPLATE = ' <tr style="border-top: 1px solid black;">\n <td class="request_type">$http
static/templates/row.html
```

```
bottle_gui.bottle_gui.DESCR_TEMPLATE = '\n <tr>\n <td class="blank_td">&rarr;</td>\n <td class="method_descri'
static/templates/descr.html
```

```
class bottle_gui.bottle_gui.RouteInfo (method, path, args, docstring, mdocstring, module_name)
```

Bases: object

Container for informations about *route*.

## method

*fn reference*

Reference to undecorated function.

path

$$str$$

Path to the function in bottle.

**args**

*list*

Args of the function.

**docstring**

*str*

Docstring for the function.

**mdocstring**

*str*

Docstring for the module where the function is.

**module\_name**

*str*

Name of the module where the function is.

Attributes method (fn reference): see Attributes section for details. path (str): see Attributes section for details. args (list): see Attributes section for details. docstring (str): see Attributes section for details. mdocstring (str): see Attributes section for details. module\_name (str): see Attributes section for details.

**to\_html()**

Convert informations about this route to HTML.

---

**Note:** `DESCR_TEMPLATE` and `ROW_TEMPLATE` is used.

---

**Returns** HTML representation of the *route*.

**Return type** str

**to\_dict()**

Return dictionary representation of the class. This method is used for JSON output.

**Returns** Dictionary following keys: method, path, args, docstring, mdocstring, module\_name.

**Return type** dict

**class** bottle\_gui.bottle\_gui.**RouteGroup**(*routes=[]*)

Bases: object

This object is used to group `RouteInfo` objects.

**Parameters** *routes* (list, default []) – List with `RouteInfo` objects.

**get\_path()**

Return *path* for this group.

**Returns** Path.

**Return type** str

**get\_docstring()**

Return 'module' docstring.

**Returns** Module docstring, if defined, or blank string.

**Return type** str

**to\_html()**

Convert group and all contained paths to HTML.

---

**Note:** `TABLE_TEMPLATE` is used.

---

**Returns** HTML.

**Return type** str

**to\_dict()**

Convert group to dict. This method is used for JSON output.

**Returns** {path: [routes]}

**Return type** dict

**See also:**

`RouteInfo.to_dict()`

`bottle_gui.bottle_gui.list_routes()`

Get list of `RouteInfo` objects from bottle introspection.

**Returns** `RouteInfo` objects.

**Return type** list

`bottle_gui.bottle_gui.group_routes(ungrouped_routes)`

Group list of `RouteInfo` objects in *ungrouped\_routes* by their `RouteInfo.path` properties.

**Parameters** *ungrouped\_routes* (list) – List of `RouteInfo` objects.

**Returns** `RouteGroup` objects.

**Return type** list

`bottle_gui.bottle_gui.to_html(grouped_routes)`

Convert list of `RouteGroup` objects in *group\_routes* to HTML.

**Parameters** *grouped\_routes* (list) – List of `RouteGroup` objects.

**Returns** HTML page with routes.

**Return type** str

`bottle_gui.bottle_gui.to_json(grouped_routes)`

Convert list of `RouteGroup` objects in *grouped\_routes* to JSON.

**Parameters** *grouped\_routes* (list) – List of `RouteGroup` objects.

**Returns** JSON representation of *grouped\_routes*.

**Return type** str

`bottle_gui.bottle_gui.gui(path='/')`

Run *bottle-gui* at given *path*.

**Parameters** *path* (str, default "/") – Bottle path on which the application will be available.

**Returns** fn reference: Function, which provides the *bottle-gui* functionality, mapped to bottle *path*.

`bottle_gui.bottle_gui.get_static(fn)`

Serve static files.



---

**Testing**

---

This project uses `pytest` for testing. You can run the tests from the root of the package using following command:

```
$ py.test
```

Which will output something like:

```
===== test session starts =====
platform linux2 -- Python 2.7.6 -- py-1.4.23 -- pytest-2.6.0
collected 2 items

tests/test_gui.py ..

===== 2 passed in 1.31 seconds =====
```



---

## Indices and tables

---

- *genindex*
- *modindex*
- *search*





## **b**

`bottle_gui.bottle_gui`, [5](#)



## A

args (bottle\_gui.bottle\_gui.RouteInfo attribute), 5

## B

bottle\_gui.bottle\_gui (module), 5

## D

DESCR\_TEMPLATE (in module bottle\_gui.bottle\_gui), 5

docstring (bottle\_gui.bottle\_gui.RouteInfo attribute), 5

## G

get\_docstring() (bottle\_gui.bottle\_gui.RouteGroup method), 6

get\_path() (bottle\_gui.bottle\_gui.RouteGroup method), 6

get\_static() (in module bottle\_gui.bottle\_gui), 7

group\_routes() (in module bottle\_gui.bottle\_gui), 7

gui() (in module bottle\_gui.bottle\_gui), 7

## I

INDEX\_TEMPLATE (in module bottle\_gui.bottle\_gui), 5

## L

list\_routes() (in module bottle\_gui.bottle\_gui), 7

## M

mdocstring (bottle\_gui.bottle\_gui.RouteInfo attribute), 6

method (bottle\_gui.bottle\_gui.RouteInfo attribute), 5

module\_name (bottle\_gui.bottle\_gui.RouteInfo attribute), 6

## P

path (bottle\_gui.bottle\_gui.RouteInfo attribute), 5

## R

read\_template() (in module bottle\_gui.bottle\_gui), 5

RouteGroup (class in bottle\_gui.bottle\_gui), 6

RouteInfo (class in bottle\_gui.bottle\_gui), 5

ROW\_TEMPLATE (in module bottle\_gui.bottle\_gui), 5

## T

TABLE\_TEMPLATE (in module bottle\_gui.bottle\_gui), 5

TEMPLATE\_PATH (in module bottle\_gui.bottle\_gui), 5

to\_dict() (bottle\_gui.bottle\_gui.RouteGroup method), 7

to\_dict() (bottle\_gui.bottle\_gui.RouteInfo method), 6

to\_html() (bottle\_gui.bottle\_gui.RouteGroup method), 6

to\_html() (bottle\_gui.bottle\_gui.RouteInfo method), 6

to\_html() (in module bottle\_gui.bottle\_gui), 7

to\_json() (in module bottle\_gui.bottle\_gui), 7